

DESCRIPTION	MEDIUM DUTY MANUAL FEED			HEAVY DUTY MANUAL FEED			MANUAL VERTICAL SLICER	MANUAL GRAVITY FEED GEAR DRIVEN SLICER	SEMI-AUTOMATIC SLICER	FULLY AUTOMATIC SLICER	HERITAGE FLYWHEEL SLICER	
	MODEL NUMBER	NS220	NS250	NS300	NS250HD	NS300HD	NS350HD	NS300V	NS350HDG	NS350HDS	NS350HDA/X	NS330M
Suited to	Type of Establishment	• Restaurants	• Smaller shops	• Delis	• Restaurants	• Supermarkets	• Delis	• Restaurants • Supermarkets • Delis	• Large restaurants • Supermarkets • Delis • Butchers	• Large restaurants • Supermarkets • Delis • Butchers	• Large restaurants • Supermarkets • Delis • Butchers	• Showpiece machine for artisan delis and restaurants
	Output	Smaller volume			Moderate volume			For high volume	For high volume	For high volume	For high volume	Smaller output for delicate cold cuts
	Types of foods	Variety of medium weight meats			Wide variety of heavy to medium weight meats			Shaving & slicing delicate cured meats and handles thick cheese	Wide variety of heavy to medium weight meats. Machine can cut very thick slices	Wide variety of heavy to medium weight meats	Wide variety of heavy to medium weight meats	Shaving prosciutto or very fine cold cut meats
Operation	Machine duty	Medium	Medium	Medium	Heavy	Heavy	Heavy	Heavy	Heavy	Heavy	Heavy	Heavy
	Operation	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Semi-automatic, basic electronic selector	Fully automatic, electronic selector with slice counter device	Manual
	Carriage movement	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Two-speed, three length options	Variable speed and length	Manual - carriage moves inwards proportionately to flywheel rotation
	Angle of feed	70°	70°	45°	45°	45°	45°	90° (straight)	52°	52°	45°	90° (straight)
	Drive transmission	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Gear	Belt	Belt	Manual gear
Specifications	Blade diameter	220 mm	250 mm	300 mm	250 mm	300 mm	350 mm	300 mm	350 mm	350 mm	350 mm	330 mm
	Height of cut	155 mm	170 mm	220 mm	170 mm	220 mm	250 mm	210 mm	250 mm	230 mm	260 mm	215 mm
	Length of cut	220 mm	220 mm	260 mm	260 mm	290 mm	290 mm	290 mm	365 mm	250 mm	330 mm	270 mm
	Slice thickness	0 - 13 mm	0 - 13 mm	0 - 13 mm	0 - 13 mm	0 - 14 mm	0 - 14 mm	0 - 14 mm	0 - 22 mm	0 - 14 mm	0 - 14 mm	0 - 4 mm
	Blade speed	290 RPM	290 RPM	310 RPM	310 RPM	300 RPM	300 RPM	310 RPM	210 RPM	300 RPM	210 - 280 RPM	NA
	Motor power	180 Watts	180 Watts	250 Watts	250 Watts	370 Watts	370 Watts	370 Watts	370 Watts	390 Watts	570 Watts	NA
	Current	< 2 Amps	< 2 Amps	< 2 Amps	< 2 Amps	< 2 Amps	< 2 Amps	< 2 Amps	< 2 Amps	< 2 Amps	< 3 Amps	NA
	Voltage (AC)	230 V	230 V	230 V	230 V	230 V	230 V	230 V	230 V	230 V	230 V	NA
Net weight	14.5 kg	16 kg	20 kg	19 kg	29 kg	36 kg	31 kg	42 kg	46 kg	50 kg	62 kg + 80 kg (optional stand model NSCIS)	