

SAM4s SAP-6600

15" Touch Screen Android POS System













Bar & Nightclub

Retail Fashion

Takeaways

Bistro & Coffee Shops

The **Sam4s SAP-6600** Android 6 (Marshmellow) powered POS Terminal with a premium look and feel comes with a 15" high definition PCT touchscreen, but at a price to meet any budget. With Intel Celeron N3160 Quad Core processor on-board this powerful terminal will meet the high demands of any retail or hospitality environment.

CPU Benchmark Comparison

Intel Celeron N3160 Quad Core 2.24 Ghz Intel Celeron J1900 Dual Core 2.43 Ghz Intel Celeron 1037U Dual Core 1.80 Ghz Intel Celeron N2807 Dual Core 2.16 Ghz



SAP-6600 PROCESSOR

SAM4s

SAP-6600

15" Touch Screen Android POS System

Incorporating a true flat LED PCT touch panel for vivid colours with the added reliability that PCT touch panels are renowned for, the Sam4s SAP-6600 Android POS provides outstanding value for money.

The touchscreen technology that drives the unit is designed with efficiency in mind – low power consumption ensures the SAP-6600 is economical and full PCAP technology ensures the touchscreen is highly responsive.













Noise-Free Fanless CPU.



Multi-Touch Panel.



VESA Wall Mount Option.

SAM4S SAP-6600 SPECIFICATION

Processor Intel Celeron N3160 (Quad Core up to 2.24Ghz).

Chipsets S0

Graphic Integrated Intel HD Graphics.

Data Storage Device M2 SSD 16GB.

Memory DDRIII SODIMM 1 Slot (up to 8GB).

BIOS AMI (America Megatrends Inc.) UEFI BIOS (Touch Available in the BIOS).

Display Size: 15" (38.1cm) 1024 x 768 Resolution LED LCD.

Supports Colours 16.2M Colours.

Contrast Ratio 500:1.

Touch Panel 15" Projective Capacitive Touch.

Interface Serial (COM4). Transparency 80%.

OS Android 6.0 (Marshmellow).

I/O Interface COM (Serial) Port D-SUB 9P x 2 Ports / RJ-45 x 1 Port.

 $5V\slash\$ 2V or RI Outputs Through COM 1, 2, 3 (BIOS Setup).

USB USB 2.0 x 2 Ports / USB 3.0 4 Ports.

Ethernet Port 10M / 100M / 1GB LAN RJ-45 x 1 Port.

VGA Port D-SUB 15P x 1 Port. Audio Port Line-Out x 1 Port.

DC Output Port 12V DC-OUT 2.5ø x 1 Port. Optional Wi-Fi and Bluetooth Module.

Booting Device M2 SSD.

Power Supply Input AC 100-240V / 50-60Hz, 2A.

Output DC 12V / 5A (DC Symbol). W x D x H 379 x 264 x 362mm.

Dimensions W x D 6.0 Kg.

Operating Temperature 0-40°C (TMA: 40°C).



YOUR LOCAL DEALER IS

SAM4S

Distributed in the UK & NI by YCR Distribution Ltd. 01924 438238. Whilst every effort has been made to provide current photographs, descriptions and specifications the manufacturers reserve the right to change specifications, illustrations, model number and appearance of any item without prior notifications and therefore will not be held responsible for any variations.