

# Hecto POS



VESA Mount Capable<sup>#</sup>



Easy Cable Management  
Fanless Diecast Casing  
Magnetic Cover Plate



LCD Customer Display\*



350% Better Performance  
Intel Celeron J6412 (Win 11 Capable)

**SENIOR**

\* Available in 8"/10"/15"

<sup>#</sup> Mounting poles/brackets for VESA mount not included



## SPECIFICATIONS

### Hecto POS

PROCESSOR	Intel Quad Core Celeron J6412 2.0 GHz (up to 2.6 GHz)
SYSTEM MEMORY	4 GB DDR4 SODIMM RAM (up to 16 GB)
STORAGE	1 x 2.5" removable SATA HDD/SSD

## DISPLAY

SIZE / RESOLUTION	15" TFT LCD / 1024 x 768 pixels
BRIGHTNESS	300 cd/m <sup>2</sup>
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

## I/O INTERFACE

USB PORT	4 x USB 3.0, 2 x USB 2.0
SERIAL PORT	3 x RJ50 (0/5/12 V selectable)
VIDEO PORT	1 x VGA
AUDIO PORT	1 x mic-in / line-out (combined)
NETWORK PORT	1 x RJ45 10/100/1000 Mbps
CASH DRAWER PORT	1 x RJ12 (12 V by default, optional 24 V by adapter)

## OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11
---------	----------------------

## ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	505 (W) x 417 (H) x 180 (D) mm   4.6 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing
VESA PATTERN	100 x 100 mm
TEMPERATURE	Operating: 0°C to 35°C   Storage: -15°C to 60°C
HUMIDITY	Operating: 20% to 85%   Storage: 20% to 85% (non-condensing)
POWER CONSUMPTION	12 V / 5 A, external power adapter, 100-240 V, 50/60 Hz

## MODEL OPTIONS

INTEGRATED CARD READER	3-track MSR
CUSTOMER DISPLAY	8"/10"/15" TFT LCD display (1024 x 768 pixels)
SPEAKER	2 x 2 W

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



Proudly Sold & Serviced By:  
**Able Scale Co Pty Ltd**  
 Ph: 1300 731 360

21 Green St Thomastown VIC. 3074

find us on the web: [www.ablescale.com.au](http://www.ablescale.com.au)



**Quality. Safety. Versatility.**