POS RECEIPT PRINTER

### EPSON TM-U220 PRINTER



# The New Industry-wide Standard in Printing

- Outstanding Compatibility
- Easy Operation
- Higher Printing Speed
- Superior Versatility













## The New Industry-wide Standard in Printing

The TM-U220 is the easy to use yet powerful successor to the TM-U210, whose ease-of-use and reliability have made it an overwhelming favourite around the world.

#### **Outstanding Compatibility**

The TM-U220 printers are designed to be compatible with existing systems built around a TM-U210. These systems can be upgraded simply by dropping in a TM-U220. Moreover, since the external dimensions are nearly identical, there is no need to change the installation environment. The transition to the new model is as smooth as can be.

#### **Easy Operation**

Free busy operators from troublesome roll paper and ribbon cassette replacement. The TM-U220 makes these chores a snap. Simply pop the cover, drop in the paper or ribbon, shut the cover. You're back in business.

#### **Higher Printing Speed**

A full 30% faster than its predecessors, the TM-U220 printers provide high-efficiency throughput. Retailers can hand receipts to customers faster. Restaurant kitchens can receive orders quickly.

#### Superior Versatility

The versatile TM-U220 suits a wide range of needs and applications. Each type is powerful, yet compact enough to fit in confined spaces. The wall-mountable Type B and Type D free up valuable counter space in kitchens and other tight locations. Moreover, both Type B and Type D handle your choice of 58, 69, or 76 mm width roll paper.

MODEL Item	Standard Device / Unit	Applications	Appearance
Type A	Take up / Automatic cutter	Receipt & Journal Printer	
Type B	Automatic cutter	Kitchen Receipt / Ticket	
Type D		Receipt	















**SYDNEY**3 Talavera Road
North Ryde NSW 2113
Tel: 1300 304 767
Tel: (02) 8899 3666
Fax: (02) 8899 3777

ABN 91 002 625 783 07/03

Visit our website.

www.epson.com.au www.epson.co.nz

POS RECEIPT PRINTER

# Specifications



PRINT METHOD	9-pin, Serial Impact Dot Matrix
PRINT FONT	
FONT COLUMN CAPACITY (COLUMNS) CHARACTER SIZE (MM) CHARACTER SET	7 x 9 / 9 x 9 40 / 42 or 33 / 35 1.2 (W) x 3.1 (H) / 1.6 (W) x 3.1 (H) 95 Alphanumeric, 37 International, 128 x 12 Graphic, Traditional / Simplified Chinese
CHARACTERS PER INCH	Thai, Japanese, Korean 17.8 / 16 cpi or 14.5 / 13.3 cpi
INTERFACES	17.57 To opt of 14.57 To 5 opt
III AOLO	RS-232, Bi-directional parallel, Dealer Option: USB, 10 Base-T I/F
DATA BUFFER	4 KB or 40 bytes
PRINT SPEED	
	4.7 lps (at 40 columns, 16 cpi), 6.0 lps (at 30 columns, 16cpi)
PAPER	
DIMENSIONS (mm)	$57.5 \pm 0.5$ , $69.5 \pm 0.5$ , $76.0 \pm 0.5$ (W) x dia. $83.0$
THICKNESS (mm)	0.06 to 0.085
COPY CAPABILITY	One original and one copy
INKED RIBBON	ERC-38 (Purple, Black, Black / Red)
RIBBON LIFE	£
	Purple: 4 x 10 <sup>6</sup> characters, Black: 3 x 10 <sup>6</sup> characters, B / R: 15 x 10 <sup>5</sup> characters (Black), 75 x 10 <sup>4</sup> characters (Red)
POWER	AC adaptor (included)
POWER CONSUMPTION	Approx. 31 W
D.K.D. FUNCTION	2 drivers
RELIABILITY	
MTBF MCBF	18 x 10 <sup>4</sup> hours 18 x 10 <sup>6</sup> lines
OVERALL DIMENSIONS (mm)	
	Type A: 160 (W) x 286 (D) x 157.5 (H)  Type B: 160 (W) x 248 (D) x 138.5 (H)  Type D: 160 (W) x 248 (D) x 138.5 (H)
WEIGHT (APPROX.)	, , , , , , , ,
	Type A : 2.7 Kg Type B : 2.5 Kg Type D : 2.3 Kg
EMC STANDARDS	Type D . 2.3 Ng
Emo diniuniud	VCCl class A, FCC class A, CE marking, AS / NZS 3548 class B
POWER SUPPLY	Exclusive AC adaptor (included)
FACTORY OPTION	Near-end sensor
OPTION	Wall-hanging bracket WH-10
SAFETY STANDARDS	UL / CSA / TÜV (EN60950)





Proudly Sold & Serviced By:

Able Scale Co Pty Ltd Ph: 1300 731 360

21 Green St Thomastown VIC. 3074

find us on the web: www.ablescale.com.au